

Product Data Sheet

NewPro Remover for plastics

PRODUCT DESCRIPTION

NewPro Remover for plastics is an efficient high performance cleaner for synthetic surfaces based on the latest technology. Its innovative mode of action causes a swelling and flaking of the lacquer and leads to a quick and clean result.

NewPro Remover for plastics has been developed especially for the removal of graffiti from synthetic surfaces (polymers) and foils. Since conventional graffiti removers often corrode synthetics, blur surfaces or lead to stress corrosion. **NewPro Remover for plastics** has been developed in order to create a product which enables a gentle removal of paint from synthetic surfaces. Before applying **NewPro Remover for plastics** to larger surfaces the product should be tested in an inconspicuous area, Due to the multitude of different synthetics corrosion can not be completely eliminated.

NewPro Remover for plastics may cause clouding on polystyrene (PS), Damages caused by the graffiti attack can not be removed by NewPro Remover for plastics, **NewPro Remover for plastics** should not be used on synthetic surfaces being under high stress because these surfaces tend to stress corrosion.

NewPro Remover for plastics is based on components from renewable raw materials, is biodegradable after adding water and does not contain halogenated solvents,

NewPro Remover for plastics is intended for industrial use and may be stored for 36 months from date of production (see label).

GUIDE TO USE

NewPro Remover for plastics should be applied undiluted onto a preferably dry surface using a cloth, cotton pad or absorption sponge. It should be applied directly to the stained surface, (When mixed with water mode of action will be stopped!)

Use a paper cloth to scrub gently over the surface until the paint is fully removed. Ideal processing temperature: 10 to 30 °C. * .

Attention: Do not allow **NewPro Remover for plastics** to dry,

Finally use a paper cloth to rub the surface clean.

* Temperatures below 10 °C cause extended reaction time.

NOTE

Best cleaning performance is achieved through a combination of NewPro cleaning products and **NewPro cleaning sponges surfiMAX**.

Walls and facades can be protected from paint vandalism and resulting damages with **NewPro Graffiti Protection Sacrificial** layers sufficiently!

Surfaces that are polluted unsightly through particulate matter, soot and grease can be cleaned deeply with **NewPro Remover Plus**. Due to its innovative mode of action treated surfaces are stain-resistant throughout several months.

IMPORTANT NOTES



We recommend the use of working clothes, protective gloves and safety goggles!

In case of skin contact, clean the skin with water.

Avoid eye contact! In case of eye contact rinse with water thoroughly. Keep eye lid open. Seek medical advice from your oculist.

Please follow the instructions in the safety data sheet for proper use, storage and disposal!

Should be stored in the original containers only!

The data of the safety data sheet are up to date. All data are subject to change in the future without prior note.