

Product Data Sheet

NewPro-Osnalith AC Street Marker Paint white Article No. 6983-91210-09

Product description

NewPro-Osnalith AC Street Marker Paint white is an airdrying, aromatics-free highsolids one-component paint with good physical and chemical properties to mark streets according to BAST Prüf-Nr. 2007 1 DS 05.04

Physical Properties

Color: white
Density: 1,60+/-0,05kg/dm³
Viscosity: 33-40 s DIN-cup 53211-6 (20°C)
Dry Matter: min. 75 %

Application

We advise using the spraying method with standard machines or by painting and coating.

Dilution

With regard to temperature and application, the 0-1% NewPro OS AF Special Thinner for NewPro Osnalith products can be used, it is also free of aromatics, article no. 0059-00340.

Drying Time

Approx. 10 minutes (BAST norm: Tⁿ – air and surface temperature 15°C, relative humidity 70%, wet-film 400 µm), bad climatic conditions will increase the drying time.

Operating Conditions

Dry surface, min. air temperature +8°C, humidity max. 80%, surface temperature min. 7°C.

Retroreflexion

The retroflesive property of the marker is achieved by scattering glass reflex pearls (0,25-0,30) kg/m³ at most 5 second after paint application.

Container Size

Hobbocks 30 kg

Storage

Product can be stored in original containers at 20°C up to one year.