

Product Data Sheet

Single Component Primer

NewProProtect - High Solid Primer

Description:

High-quality, single-component, solvent-reduced and quick drying anti-corrosion primer based on special alkyd resins.

Information:

Please choose NewProProtect, Art.-Series 73006-Colour Shade in the case of low flame spread abilities being required and the approval for use on sea-going vessels in accordance with EU-Directive 96/98/EG,

Volume- Solids approx. %: 60

Density g/ml (approx.) 1,650

Dry Film Thickness: 80 µm

Theoretical Coverage : 7,5 m²/l

Packing: 10 Litres or 33kg

Colour Shade (Article-Number):

Colour Tone - 73215

Red-brown - 83480

Pebble-grey - 72240

White - 91270

Dark-yellow - 12360

Further colour shades are available on request.

Thinners:

03069-00070 (for a smooth surface)

03089-00580 (for improved drying abilities)

NewProProtect - Special

Description:

High-quality, single-component primer based on epoxy resins, quick-drying. Recoatable with single-pack finishing coats or 2-components polyurethane/acrylic finishing paints but **not** epoxies.

Also as adhesion promoter on galvanised prepared surfaces and suitable as primer for Day-Glow colours.

Volume- Solids approx. %: 43

Density g/ml (approx.) 1,33

Dry Film Thickness : 40 µm

Theoretical Coverage: 10,75 m²/l

Packing: 10 Litres

Colour Shades (Article-Number):

Colour Tone - 73038

Red-brown - 81300

Pebble-grey - 72240

White - 91500

Thinners: 03089-00580

NewProVINYL Primer TF

Description:

Single-Component tar-free, vinyl-based protective primer for areas above and below the water line. Especially suitable as an adhesion promoter over old antifouling coats.

Volume- Solids approx. %: 48

Density g/ml (approx.) 1,41

Dry Film Thickness : 75 µm

Theoretical Coverage : 6,4 m²/l

Packing: 20 Litres

Colour Shade (Article-Number):

Colour Tone - 73033

Red-brown - 81390

Silver-grey - 72420

Black - 91280

Thinners:

03089-09200

NewPro – Neue Produkte & innovative Ideen für Oberflächen und Reinigung
Lutz-Henning Robitzsch
Ricarda-Huch-Weg 2 D-40789 Monheim a. Rhein
Tel: +49 (0) 2173/964280 Fax: +49 (0) 2173/964282
eMail: news@newpro.de Internet: www.g-pro.com

**GRAFFITI
MAGIC**



NewProBLACK

Description:

Single-Component corrosion protection coating based on selected hydrocarbon resins for surfaces above and below the water line.

Volume- Solids approx. %: 41

Density g/ml (approx.) 1,13

Dry Film Thickness: 50 µm

Theoretical Coverage: 8,2 m²/l

Packing: 20 Litres

Colour Shade (Article-Number):

Colour Tone - 53214

Black - 91440

Thinners:

03089-00580

NewProBLACK AL

Description:

Single-Component protective coating based on selected hydrocarbon resins with aluminium powder for areas above and below the water line.

Volume- Solids approx. %: 41

Density g/ml (approx.): 1,12

Dry Film Thickness: 50 µm

Theoretical Coverage: 8,2 m²/l

Packing: 20 Litres

Colour Shade (Article-Number):

Colour Tone - 53214

Aluminium-brown - 91840

Aluminium-light - 91340

Thinners:

03089-00580