

Product Data Sheet

NewPro-GSE 60 Shadow Remover - The Graffiti Remover for Porous Surfaces

Product Description

NewPro-GSE 60 Shadow Remover is a remover, which was specially designed for the removal of shadows and traces of graffiti markers, graffiti, spray can ghosts, and other soiling on porous surfaces.

Range of Application and Use

NewPro-GSE 60 Shadow Remover is applied as an environmentally friendly remover for the thorough removal of graffiti shadows, graffiti and other soiling on porous surfaces such as the grooves between tiles.

Product Characteristics

NewPro-GSE 60 Shadow Remover is especially distinguished by its beautifying, highly productive and environmentally safe removal of graffiti.

Further characteristics include:

- Easy to use
- Effortless removal of stubborn stains or soiling
- Fast-acting
- Inhibits recurring stains or soiling
- Multipurpose application
- Odorless.

Instructions Regarding Use/Application

Surface preparation:

All surfaces must be sustainable, clean and free from loose particles or particles which would impair adhesion, as the NewPro-GSE 60 Shadow Remover requires.

Mixing Instructions:

NewPro-GSE 60 Shadow Remover is delivered directly ready-to-use. NewPro-GSE 60 Shadow Remover is not mixable and cannot be diluted with water or other foreign substances. Any mixture affects the cleaning properties negatively.



Instructions Regarding Use/Application

Application:

1. NewPro-GSE 60 Shadow Remover can be applied using an airless spraying device or can be applied using a clean brush.
2. Allow NewPro-GSE 60 Shadow Remover approximately 5 to 10 minutes to take effect until after a short time the graffiti shadow is dissolved.
3. Wash the dissolved graffiti contamination off with hot water with a high-pressure spray.

After drying, the surface, which has been treated with NewPro-GSE 60 Shadow Remover, can immediately be used again.

Machine Application:

NewPro-GSE 60 Shadow Remover can be applied using a standard airless spraying device. Before use, please pay careful attention to the manufacturer's operating instructions.

Notice:

NewPro-GSE 60 Shadow Remover offers a wide range of applications. For this reason, we recommend that the user carry out his/her own test to determine the suitability of the product.

For further notices, warnings or cautions, please refer to the product safety sheets of the product.

Use:

- It depends on the degree of soiling or contamination and the structure of the subsurface of the surface.

An exact amount of material needed should be determined by applying a test coating to the surface of the object.

Required Conditions for Use/Application

The application and drying requires a surface and area temperature between min. +5°C and max. +30°C. NewPro-GSE 60 Shadow Remover may not be applied under direct sunlight at temperatures over +5°C.

Period of Effect:

- Approximately 5 to 10 minutes (at approximately +20°C).

Depending on the degree of soiling or contamination and the structure of the subsurface of the surface.

Cleaning of tools:

- In freshly used condition, clean with water.

Delivery Form

Units Per Package:

- Units per package with 1 Liter or 5 Liter.

Further types and sizes of packaging and colors are available upon request.

Color:

- Colorless.

Special Instructions

Transport:

- Unlabeled and non-hazardous.

Storage:

- Minimum 6 months when stored at room temperature tightly sealed in original packaging
- Protect against moisture, frost and heat.

Work Hygiene

Before breaks and at the end working with the product, wash hands thoroughly. Do not eat, drink or smoke during use. Avoid eye and skin contact with the product. If necessary, wear protective clothing.

For further safety and protective measures please see the product safety sheets of the product.

Safety Precautions

Keep away from children. Keep containers sealed tightly closed. In the event of eye contact, immediately flush eyes out with water. In the event of skin contact, wash skin thoroughly with water and soap. Do not smoke during application and use. If swallowed seek immediate medical advice and show the packaging or product label to the treating physician.

For further safety precautions, please refer to the safety product sheets of the product.

Safety and Protective Measures

The general safety precautions for water solvent materials are to be considered.

Keep away from children. Keep containers sealed tightly closed. In the event of eye contact, immediately flush eyes out with water. In the event of skin contact, wash skin thoroughly with water and soap. Do not smoke during application and use. If swallowed seek immediate medical advice and show the packaging or product label to the treating physician.

The technical advice regarding the use and application of our products is the result of extensive research and development as well as many years of experience, according to the best of our knowledge. The different kinds of requirements of an object, under varying conditions, make it necessary for the user to check the suitability for the intended purpose. We reserve the right to effectuate changes, which serve to affect the technical advance or improvement of our product.

For further safety precautions, please refer to the safety product sheets of the product.

The product is only designed for commercial use and application!

Dated: 27.04.2006