

## **Produktdatenblatt**

### **NewProAqualine**

### **Water-Soluble Coating Agents**

#### **NewProPOX Aquacoat**

##### **Description:**

Water-soluble, 2-component epoxy resin primer and intermediate coat for surfaces above and below the water line.

Suitable for example for up grading an existing shop primer, as holding primer for freshly sand-blasted surfaces and as a sealer on galvanized, a wide range of non-ferrous and GRP surfaces.

##### **Information:**

Mixing Ratio: 8,8 l Basis : 1,2 l Hardener 03091-65600

**Volume- Solids approx. %:** 41

**Density g/ml (approx.)** 1,25

**Dry Film Thickness:** 75 µm

**Theoretical Coverage:** 5,5 m<sup>2</sup>/l

##### **Packing:**

- 10 Litres

##### **Colour Shade (Article-Number):**

Colour Tone-2065 - 63509

Pebble-grey - 73520

Dark-yellow - 12360

Grey-White - 93690

##### **Thinners:**

03089-11520

NewPro – Neue Produkte & innovative Ideen für Oberflächen und Reinigung

Lutz-Henning Robitzsch

Ricarda-Huch-Weg 2 D-40789 Monheim a. Rhein

Tel: +49 (0) 2173/964280 Fax: +49 (0) 2173/964282

eMail: [news@newpro.de](mailto:news@newpro.de) Internet: [www.g-pro.com](http://www.g-pro.com)

**GRAFFITI  
MAGIC**



## **NewProDUR Aquatop**

### **Description:**

Water-soluble, 2-component PUR-Acrylic high gloss finishing coat. High weather resistance and gloss stability. Good workability also with brush or roller. Suitable for dry film thicknesses up to 50 µm

### **Information:**

Mixing Ratio: 10 kg Basis : 2 kg Hardener 03041-45563

**Volume- Solids approx. %:** 49

**Density g/ml (approx.)** 1,25

**Dry Film Thickness :** 40 µm

**Theoretical Coverage :** 9,8 m<sup>2</sup>/kg (12,3 m<sup>2</sup>/l)

### **Packing:**

- 12 kg

### **Colour Shade (Article-Number):**

Colour Tone-0047 - 03540

Further colour shades are available on request.

### **Thinners:**

03089-11520