

Product Data Sheet

NewPro WR 17 Cement Haze Remover

NewPro WR 17 Cement Haze Remover against persistent soiling like cement haze, rust, mortar droppings, and lime scale.

Product Description

NewPro WR 17 Cement Haze removes persistent soiling. It is a sub-acid liquid power cleaner to remove persistent soiling like cement haze, rust, mortar droppings as well as lime scale.

NewPro WR 17 Cement Haze Remover for persistent soiling is not suitable for marble, lime stone, anodized surfaces, and acid-sensitive tiles.

Instructions

NewPro WR 17 Cement Haze remover for persistent soiling has to be diluted with cold water in a 1:1 to 1:10 ratio depending on the degree of soiling. Apply with a brush onto the surface and let react for a short time. Then rinse thoroughly with clean water.

NewPro WR 17 Cement Haze Remover needs to be tested before application at an inconspicuous spot. NewPro WR 17 Cement Haze Remover must only be used with acid-resistant materials.

Packaging Size:

1 Liter and 5 Liters

Safety Advice According to German Hazardous Substances ordinance (GefStoffV):

In case of eye contact rinse immediately and thoroughly with water and consult a physician.

When working with product wear appropriate protective clothing, gloves, goggles and face protection.

In case of accident or discomfort consult a physician immediately and show product label if possible.

Risk Phrase According to German Hazardous Substances ordinance (GefStoffV):

Product causes skin irritation. After direct contact danger of damage to the eyes.

Ingredients According to EC-Advice

5-15 % phosphoric acid, 5- 15 % hydrochloric acid, 5-15 %, 5 – 15 % non-ionic surfactants, solvents Product is bio-degradable according to EC regulations.